

10.1" LCD touch skærm alu front, Projected
Capacitive touch 1280x800 16:10, IP66 front, DC
9~36V

FEATURES

- 10.1" TFT 1280x800 (16:10)
- Frontpanel IP66 standard / IP69K option
- Aluminium kabinet
- VGA, DVI, HDMI og DP input
- Forsyningsspænding: DC 9 ~ 36V
- Kontrast: 800:1
- Lysstyrke: 350 nits standard / 1000 nits option
- Touch via USB: Projected Capacitive standard / Resistive option / ingen touch option
- Touch via RS232: option
- VESA 100 og panel Mount
- Dimensioner: 285 x 189 x 48.9mm
- Vægt: 1,9 kg
- Driftstemperatur: 0 ~ +50°C standard / -20 ~ +60°C option



SPECIFICATIONS

Andet	:	15G peak acceleration (11 msec. duration) / Operation
Drivere	:	eGalaxTouch
Forsyning	:	DC 9 ~ 36V
Indgang	:	USB
IP-Tæthed	:	IP66 front
Kabinet	:	Aluminum die-casting chassis
Montering	:	Panel and VESA
Opløsning	:	1280x800 16:10
OS SUPPORT	:	Windows XP, Vista, 7, 8, CE, Mac og Linux
Touch	:	USB, PCAP
VESA standard	:	100 x 100mm
Vægt	:	1.9 kg





DANBIT

MON10.1-TFT-T

SPECIFICATIONS



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.