

SDI4MULTI-G

4 ports SDI splitter, SD-SDI, HD-SDI, 3G-SDI. 1 x BNC input og 4 x BNC output. Samme output billede. 5VDC
FEATURES

4 ports SDI multimedia splitter
Samme billede på de 4 monitorer, op til 100 meter
Kompatibel med SD-SDI, HD-SDI og 3D-SDI
5 x BNC hun
1 x BNC - SDI input
4 x BNC - SDI output
SD 525i and 625i
HD 720p 24/25/30/50/60Hz, HD 1080i 50/60Hz
HD 1080p 24/25/30/50/60Hz
Forsyningsspænding: 5VDC PSU medfølger
Mål: 130 x 77 x 24 mm



SPECIFICATIONS

Driftstemperatur	:	0~+60 °
Afstand	:	p til 100 m kabellængde v. 3G-SDI (2,97 Gb/s) på ind- og udgangene
Andet	:	Power consumption: 250mA (DC 5V)
Kompatibilitet	:	SD-SDI, HD-SDI og 3G-SDI
Opløsning	:	Op til 1920 x 1080i/p ved 60 Hz
Output	:	SDI signal output amplitude: 800mVp-p
Strømforsyning	:	Forsynes af medfølgende 5 VDC 1 A netadapter
Udgange	:	4 x BNC hun, indgange: 1 x BNC hun
Dimensioner	:	130 x 77 x 24mm (L x W x H)

