

USB til 1 x RS232 / RS422 / RS485 adapter, optisk isoleret

FEATURES

- Få en RS485 eller RS422 eller RS232 port på PC via USB porten
- Galvanisk isolation (optisk) 2KV
- DB9 han og skrue-terminal til 232 / 422 / 485 tilslutning
- Terminering med Jumpere
- Baudrate 300bit/s to 921,6 Kbit/s
- Valg mellem RS232, RS422 og RS485 med DIP switch
- Supporterer Win7/8/10 og over samt MAC, Linux
- Forsynes via USB (5V)
- Driftstemp. 0° til 55°C



SPECIFICATIONS

USB	:	USB 2.0 High Speed, USB 1.1 compliant Speed 480Mbps, hi-speed USB
Driftstemperatur	:	0°C to 55°C (32°F to 131°F)
Approval	:	CE, FCC
Baudrate	:	Data Bits 7, 8 Parity None, Even, Odd, Mark, Space Stop Bit 1, 2 Flow Control Hardware (RTS, CTS), XON/XOFF
Isolation	:	25kV ESD protection for all signals 2000V DC optical isolation for all signals
Kabel	:	USB kabel medfølger
Kabel	:	0,9 m
Luftfugtighed	:	5% to 95% RH
Materiale	:	Casing SECC metal chassis with DIN rail bracket
Montering	:	DIN rail bracket
OS SUPPORT	:	Windows 2000 up to Windows 10 Windows Server 2000 up to 2018 Linux kernel 2.6+ Mac OS X support available
Porte	:	Max. Speed RS-232:up to 1Mbps RS-422/485:up to 3Mbps RS-232 Signals RxD, TxD, GND, RTS, CTS RS-422 Signals TxD-, TxD+, RxD+, RxD-, GND, RTS-, RTS+, CTS+, CTS- RS-485 Signals (4 wire) TxD-, TxD+, RxD+, RxD-, GND RS-485 Signals (2 wire) Data-, Data+, GND



SPECIFICATIONS

Stik	:	Skrue
Strømforsyning	:	Power Input Power supplied via USB connector No external power needed Power Output 5V, 150mA through pin 5 of terminal block
Temperatur	:	-20°C to 75°C (-4°F to 167°F)

