

1 port RS485 / 422 Serie port server. Serial Device Server med RS422 eller RS485 kan PoE forsynes

FEATURES

- 1-port RS-422/485 til Ethernet-enhedsserver
- 1x 10/100 Mbps RJ45 LAN
- DB9 han- **eller** 5-bens terminalblok seriel stik
- Baudrater: 300 til 115,2 kbps
- Konfigurerbar: 6/7/8 databits, 1/2 stopbits, paritet Ingen/Ulige/Lige
- Indbygget watchdog for pålidelig drift døgnet rundt
- Bred strømningang: 7-40 VDC (DC-stik) / PoE (48 VDC via Ethernet)
- Industrielt metalkabinet, ~300 g
- Driftstemperatur 0-55 °C; luftfugtighed 5-95 % RF
- IS-modellen tilføjer 2,5 kVrms isolation og 500 W overspændingsbeskyttelse



SPECIFICATIONS

Serial	:	Ports: 1 × RS422/RS485 / RS422 signals: TXD+, TXD-, RXD+, RXD-, GND / RS485 signals: DATA+ (A), DATA- (B), GND
Driftstemperatur	:	Operating temperature: 0 to 55 °C
Baudrate	:	300 bps to 115.2 kbps
Forsyning	:	7-40 VDC via DC jack / 48 VDC via Ethernet cable (PoE model only)
Isolation	:	Isolation: 2500 Vrms / Surge protection: 500 W
Netværk	:	1x RJ45 10/100 Mbps (auto-negotiation)
Porte	:	Serial: DB9 male (RS422/485) or 5-pin terminal block
Watchdog	:	Watchdog timer: Built-in

