

17" Panel-PC med stålfront, Intel Core i3 / i5 / i7 med 2x PCIe-udvidelse (kan leveres med 1000nits)

FEATURES

17" TFT-LCD 1280x1024

Panel montering

Touch: Standard projiceret kapacitiv, på bestilling:

Resistiv eller glas

Kontrast 800:1 standard (på bestilling: 1000:1 nits)

8. generations Intel Core Celeron, i3, i5, i7

understøttelse

1 x 260-bens DDR4 SO-DIMM-stik op til 32GB

2400MHz

4x USB 3.0 type A

2x GbE LAN

Lyd ind/ud

IP66 foran

1 x HDMI

1 x VGA

2x 2,5" SATA RAID 0,1,5 understøttelse

3x COM (1xDB9 RS-232/422/485, 1x DB9 RS232, 1x DB9 RS-422/485)

1 x Mini PCIe fuld størrelse (PCIe/USB/SATA)

1 x Mini PCIe halv størrelse (PCIe/USB)

1x SIM-slot til (wifi/BT/4G)

1x PCIe1 og 1x PCIe x16 slot.

439x348x64,8mm

CE/FCC klasse A

Arbejdstemperatur 0~50 grader

Mulighed for ekstern ON/OFF via. 2-polet stik

Bredt område DC 9 ~ 36V strømindgang

Understøtter Windows 10 IoT, Windows 11



SPECIFICATIONS

USB	:	4 x USB 3.0 Type A, 2 x USB 2.0 Type A by cable (option)
Approval	:	CE / FCC Class A
Ethernet	:	2 x GbE LAN RJ-45
Forsyning	:	DC 9~36Vdc
IP-Tæthed	:	Front IP 66
Luftfugtighed	:	10 to 90% @ 40°C, non- condensing
Lyd	:	1 x Mic-in, Line-out
OS SUPPORT	:	WIN 7, Windows 8.1, Windows 10 IOT Enterprise
Porte	:	1xDB9 RS232, 1xDB9RS232/422/485, 1x RS422/485
Skærm	:	LCD Size 17" TFT-LCD Max. resolution 1280 x 1024 Max. color 16.7M Luminance(cd/m ²) 350 Viewangle(H°/V°) 170 (H) / 160 (V) Contrast 1000: 1 Backlight lifetime(hrs) 30,000 hrs
SSD	:	2x2.5" HDD/SSD
Temperatur	:	Operating temperature(°C) 0~50°C Storage temperature(°C)



**DANBIT**

IPP17-I8+PCIEX

SPECIFICATIONS

Vægt	:	7.6Kg
Dimensioner	:	439x348x95mm



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.