

Ethernet til CAN Device Server. CAN til Ethernet gateway. Med 1 x CAN, RS232 og RS485.

FEATURES

- Internet communication controller med 1 X CAN bus, 1 X RS-232, 1 X RS-485 og 1 X Ethernet 10/100 Base-TX Ethernet controller
- TCP/IP protokol
- 80 MHz CPU
- 1 x RS-232 port, 1 x RS-485 port og 1x CAN port kan benyttes samtidig
- Max transmission speed op til 1M bps for CAN og 115.2kbps for RS-232 RS-485
- 7-segment LED display
- Software konfiguration til CAN and RS-232
- Web Konfiguration
- Op til 25 Ethernet client tilslutninger
- Supporterer Virtual COM



SPECIFICATIONS

Driftstemperatur	:	-25 ~ 75 °C
Controller	:	10/100Base-TX Ethernet Controller (Auto-negotiating, Auto_MDIX) Connector RJ-45 with LED indicator
Forsyning	:	Power supply Unregulated +10 ~ +30 VDC Protection Power reverse polarity protection, Over-voltage brown-out protection Power Consumption 2.5 W
Isolation	:	1000 VDC for DC-to-DC, 2500 Vrms for photo-couple
Montering	:	DIN-Rail
Stik	:	CAN BUS: 2-pin screwed terminal block. COM 1 Connector 5-pin screwed terminal block (TxD, RxD, RTS, CTS, GND). COM 2 Connector 2-pin screwed terminal block (DATA+, DATA-)
Dimensioner	:	(W x L x H) 72mm x 122mm x 33mm

