

ESW4SFP2

4 ports 10/100/1000Mbit RJ45 + 2 ports
100/1000Mbit SFP slot, Managed switch, 12 - 48VDC
og 24VAC

FEATURES

- Fast Ring, Redundant Ring for kritisk netværk
- IEEE 1588 Time Protocol, supporterer MEF service og synkront Ethernet
- Supporterer MODBUS TCP protocol
- Supporterer IGMP Snooping
- 4 x 10/100/1000Mbps RJ45 porte
- 2 x 100/1000Mbit SFP porte
- 12 - 48VDC, redundant input
- 24VAC forsyningsspænding er også mulig
- IP30 metalkabinet med DIN-beslag
- Temperaturområde fra -40 til +75°C



SPECIFICATIONS

Driftstemperatur	:	-40 - 75°
Forsyning	:	Dual 12~48V DC 24V AC
Materiale	:	IP30 metal case
Montering	:	DIN rail kit and wall-mount kit
Porte	:	4 10/100/1000BASE-T RJ45 auto-MDI/MDI-X ports
Slot	:	2 1000BASE-SX/LX/BX SFP interfaces (Port-5 to Port-6) Compatible with 100BASE-FX SFP
Stik	:	Removable 6-pin terminal block for power input Pin 1/2 for Power 1, Pin 3/4 for fault alarm, Pin 5/6 for Power 2
VLAN	:	802.1Q tagged based VLAN, up to 255 VLAN groups Q-in-Q tunneling Private VLAN Edge (PVE) MAC-based VLAN Protocol-based VLAN Voice VLAN MVR (Multicast VLAN Registration) Up to 255 VLAN groups, out of 4094 VLAN IDs
Dimensioner	:	32 x 87x 135 mm

