

19" TFT, marine godkendt panel monitor med IP65 tæthed, uden touch

FEATURES

- 19" TFT Marine Monitor med IP65, No Touch
- LED baggrundsbelysning
- 250 nits
- 1 x HDMI, 1 x VGA, 1 x Composite, 1 x Audio 3.5 Jack-stik
- Anti-Vibration: 5 - 500 Hz / 1 Grms PTP
- Anti-schock: 15G / Peak (11ms)
- AC Power Standard IEC Indløb 100-240V AC
- Tænd/sluk via frontknapper
- Justering af VR-lysstyrkeknop
- Power Mode Status LED-indikator
- On Screen Display Control (OSD)
- Flush Mount, VESA Mount
- Valgfrit: AR Hårdhed Glas: 3mm Anti-reflekterende beskyttelsesglas
- Valgfrit: DC Power: Isoler 12V / 24V / 48V / 125V DC Power
- Valgfrit: SR-BKT: Stand- og tagmonteringsbeslag
- Valgfrit: RT-BKT: Roterende plade robust beslag
- Valgfrit: SV-BKT: Solskærmsbeslag



SPECIFICATIONS

Driftstemperatur	:	0 - 50 deg. C
I/O	:	1 x HDMI, 1 x VGA, 1 x Composite (RCA), 1 x 3.5" jack audio
IP-Tæthed	:	IP65 tæthed
Kontrast	:	1000:1, 250 cd/m2
Materiale	:	Aluminum Front Bezel + Metal Housing
Montering	:	Panel (Flush) Mount, VESA Mount, Robust Bracket, Sun-visor Bracket
Strømforsyning	:	AC standard IEC inlet
Vægt	:	9.5 / 13 KGs
Dimensioner	:	fysiske dimensioner: 483 x 444 x 70mm. pakke: 620 x 580 x 220mm
Certifications	:	CE / FCC / RoHs / IEC60945

