

MOD485-R12-I

12 x Power relæ modul til 30VDC 5A, 250VAC 5A, RS485 bus, MODBUS/RTU/ DCON, 10 - 30VDC 2.5Watt FEATURES

- 12 kanals power relæ output modul
- RS485 til MODBUS
- Kommunikerer via MODBUS RTU
- Drifttemperatur -25°-75°C
- 4 kV EFT beskyttelse
- 3 kV Surge Protection
- Til væg eller DIN skinne montering



SPECIFICATIONS

Driftstemperatur	:	-25 ~ +75°C
Baudrate	:	1200 ~ 115200 bps
Beskyttelse	:	EFT: ± 4 kV for Power Line, Surge: ± 3 kV for Power Line
Forsyning	:	Input Range 10 ~ 30 VDC, Consumption: 1.7 W- 2.3 W
Interface	:	RS-485
Isolation	:	3750 VDC
LED	:	Yes, 12 LEDs as Digital Input/ Relay Output Indicators
Montering	:	DIN-Rail or Wall Mounting
Protokol	:	Modbus RTU, DCON
Relæ	:	12 (Form A) power relay, Rating: 5 A @ 250 VAC 5 A @ 30 VDC, Load 10 mA @ 5 V
Watchdog	:	Yes, Module (1.6 Seconds), Communication (Programmable)
Dimensioner	:	72 mm x 123 mm x 35 mm

