

Intelligent CANBUS 2.0A og 2.0B til 10/100 Base- TX Ethernet/ Modbus TCP/IP / Modbus RTU Konverter FEATURES

Intelligent CAN til MODBUS TCP/IP konverter
Understøtter både CAN-specifikation 2.0A og 2.0B
Maksimal transmissionshastighed op til 1M bps for CAN og 115,2 kbps for RS-232 RS-485
Maksimal transmissionsafstand på CAN over 1000m (følg CAN-specifikationen)
7-segment LED-display til Modul IP, RS-232 baudrate, CAN-konfiguration...
Supporterer webkonfiguration
Understøtter maksimalt 24 Ethernet-klienterforbindelse
Modbus TCP/RTU-kommando til læsning og skrivning af CAN-meddelelse
Transparent kommunikation mellem CAN-enhederne via Ethernet
30 specifikke CAN ID'er i Modbus TCP/RTU-tilstand
DIN montering



SPECIFICATIONS

Driftstemperatur	:	-25 ~ 75 °C
Andet	:	Terminator Resistor Jumper for 120 Ω terminator resistor Specification ISO-11898-2, CAN 2.0A and CAN 2.0B
Ethernet	:	10/100Base-TX Ethernet Controller (Auto-negotiating, Auto_MDIX) Connector RJ-45 with LED indicator
Forsyning	:	Unregulated +10 ~ +30 VDC
Isolation	:	1000 VDC for DC-to-DC, 2500 Vrms for photo-couple
Montering	:	DIN-Rail
Porte	:	COM 1 RS-232 COM 1 Connector 5-pin screwed terminal block (TxD, RxD, RTS, CTS, GND) COM 2 RS-485 (Self-turner inside) COM 2 Connector 2-pin screwed terminal block (DATA+, DATA-)
RAID niveau	:	CAN, Ethernet, Modbus RTU, Modbus TCP
Stik	:	CANBUS: Connector 2-pin screwed terminal block (CAN_L, CAN_H)
Dimensioner	:	72mm x 122mm x 33mm (W x L x H)

