

6 kVA / 5.4 kW Professional Online UPS til 19" Rack / Tower, inklusiv batteri-bank. Når sikkerhed skal være i top

FEATURES

6,0 kVA / 5,4 kW UPS inkl. batterier
UPS 6000VA 5400W, 176-300VAC
Model 230V: +/- 10 %, 50 Hz (+/- 0,1 %), 2 - 6 ms typisk, Simuleret sinusbølge
Alarm: UPS Status, ladeniveau, batteriniveau, Input/Output, afladning og fejlindikator
Dimensioner: 580 mm (D) x 438 mm (B) x 133 mm (H) (3U)
Til 19" rackmontage
Vægt: 17 kg



SPECIFICATIONS

Alarm	:	Battery Mode Sounding every 4 seconds Low Battery Sounding every second Overload Sounding twice every second Fault Continuously sounding
Andet	:	Single Phase with ground
Batteri	:	Battery Type / Numbers Battery Pack Voltage: 240 V Nukbers depending on the capacity of external batteries Charging Current (max.) 4.0 A Charging Voltage 273 VDC
Input	:	Voltage Range 176-300 VAC at 100% load 110-300 VAC at 75% load Frequency Range 46Hz - 54Hz or 56Hz - 64Hz Power Factor ≥ 0.99 @ Nominal Voltage (100% Load)
Kapacitet	:	6.0 kVA / 5.4 kW
LED	:	UPS Status, Load Level, Battery level, Input/Output Voltage, Discharge Timer and Fault conditions
Montering	:	19" rack
OS SUPPORT	:	Supports Windows 2000/2003/XP/Vista/2008/7/8, Linux, Unix, and MAC
Output	:	Output Voltage 200/208/220/230/240 VAC Voltage Regulation $\pm 1\%$ Frequency range (Synchronized Range) 46Hz - 54Hz or 56Hz - 64Hz Frequency Range (Batt. Mode) 50Hz ± 0.1 Hz or 60Hz ± 0.1 Hz Current Crest Ratio 3:1 (max.)
Spændingsform	:	Pure Sinewave
Stik	:	AC Input Connector Terminal AC Output Connector Terminal
Støj	:	Less than 58dBa @ 1 Meter



**DANBIT**

UPS-6KVA-RED

SPECIFICATIONS

Dimensioner : 580mm (D) x 438mm (W) x 133mm (H) (3U)



Danbit A/S Værkstedsvvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.