

3 kVA / 2,4kW UPS med LCD Display. 19" Rack / Tower. Ægte sinuskurve, inkl. batteri-boks til 6 stk. 12V/55Ah. 10 timer v/200W

FEATURES

Top klasse 3000VA / 2400W Online UPS / nødstrøm
Input: 110-300 VAC 40Hz-70 Hz
Udgangsspænding: 230 VAC / 50Hz
LCD Display
Enkelt fase
Ægte sinuskurve - støjfri udgangsspænding
DC input fra batteripack: 72VDC (6 x 12V Batt)
6 x 12VDC Batterier tilkøbes
19" Rack / Tower 2 i 1
Godkendelser: IEC 62040-1 (safety) IEC-62040-2 (EMC)



SPECIFICATIONS

Driftstemperatur	:	0-40°C
Alarm	:	Battery Mode Sounding every 4 seconds Low Battery Sounding every second Overload Sounding twice every second Fault Continously sounding
Andet	:	Optional SNMP Power management from SNMP manager and web browser
Batteri	:	6 x 12V/55Ah
Input	:	110-300 VAC 40Hz ~ 70 Hz
Interface	:	Interface to pc via Smart RS-232 / USB
Kapacitet	:	3.0 kVA / 2,4 kW
LED	:	Load level, Battery level, AC mode, Battery mode, Bypass mode, and Fault indicators
Montering	:	stander or 19" rack
OS SUPPORT	:	Windows 2000/2003/XP/Vista/2008/7, Linux, Unix, and MAC
Output	:	230 VAC
Software	:	Included



SPECIFICATIONS

Standarder	:	IEC 62040-1 (safety) & IEC-62040-2 (EMC)
Stik	:	1 x IEC 320 C20 Terminal (input) 4 x IEC 320 C13 (output)
Støj	:	Less than 50dBa by 1 Meter
Vægt	:	10 kg without batterypack
Dimensioner	:	480 (D) x 438 (W) x 88 (H) (2U) without batterypack

