DANBIT

PIR-WL-R

Modtager til PIR-WL35 - styreenhed til eksternt udendørs trådløst PIR system

FEATURES

- Modtager/ styreenhed til trådløst PIR system
- Håndterer 1-3 sensorer/ detektorer
- Forsynes via 12V dc 35mA
- Driftstemperatur -20 til +55°
- IP65 tæt til udendørs brug
- Frekvens 433 MHz - rækkevidde 150m
- Til vægmontering
- Virker ikke uden PIR sensor PIR-WL35

Danbit A/S Værkstedsvej 39 Køge, 4600 Denmark | +45 56662020 | salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.

DANBIT

PIR-WL-R

SPECIFICATIONS

Driftstemperatur	:	-20° C + 55° C
Alarm	:	Attendance reporting. Battery low and jamming indicator
Andet	:	CCTV Outputs 3 x independent channel outputs (24hr) Selectable N/O (form A) or N/C (form B) Individual timers 0.4 to 60 seconds after last detection. Non volatile memory.'A' Outputs
Forsyning	:	Requires 12V dc - 35mA
IP-Tæthed	:	High impact IP65 rated ABS housing for external mounting
Output	:	3 independent - VE switching outputs. 3 independent volt free outputs (timers 0.4 to 60 seconds). 1x photocell controlled output (timer 60 seconds)
Vægt	:	340 g
Dimensioner	:	210 x 180 x 70mm (HxWxD)

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.