

Industriel blæserløs Mini PC, DIN mount, Pentium®
N4200 1,1 / 2,5 Ghz Quad core, 3 x Gigabit LAN (2 x
PoE+ Type 2), 8~35 VDC

FEATURES

- Intel® Apollo Lake Pentium® N4200 quad-core processor
- 3x Gigabit Ethernet porte (2 x PoE+ type 2) Intel® I210 GbE
- 1x Software prog. RS232/422/485 (COM1)
- 1x RS-422/485 port (COM2) eller option: 3x 3-wire RS-232 porte
- 2x USB3.1 Gen.1
- 2x USB2.0
- 1x DVI-I
- 1x Mini-PCIe full-size (USIM Socket)
- 1x mSATA half-size (storage)
- Option: 2½" SSD/HDD mount
- DIN-Rail standard (wall mount option)
- 25° C till 70° C
- 5.6 x 15 x 11 cm



SPECIFICATIONS

CPU	:	N4200 Quad Core 1.6/2.0 GHz
USB	:	2x USB 3.0 2x USB 2.0
Driftstemperatur	:	-25°C ~ 70°C med SSD, -10°C ~ 50°C med HDD
Approval	:	CE/FCC Class A, according to EN 55022, EN55032 & EN 55024
Chok/Vibration	:	Vibration Operating, 5 Grms, 5-500 Hz, 3 Axes (w/ SSD, according to IEC60068-2-64) Shock Operating, 50 Grms, Half-sine 11 ms Duration (w/ SSD, according to IEC60068-2-27)
Ethernet	:	3x Gbit by intel I210 GBE controller (2 support POE+ Type2)
Forsyning	:	1x 3-pin pluggable terminal block for 8~35VDC DC input
Grafik	:	Integrated Intel® HD Graphics 505
Hukommelse	:	1x DDR3L-1866, op till 8GB
Luftfugtighed	:	10%~90% , non-condensing
Lyd	:	1x speaker-out, 1x microphone-in
PoE	:	IEEE 802.3at PoE+ on port #2 and #3



SPECIFICATIONS

Porte	:	1x Software-programmable RS-232/422/485 ports (COM1), 3x 3-wire RS-232 ports (COM2/3/4) or 1x RS-422/485 port (COM2)
SATA	:	1x half-size mSATA port, 1x SATA port till 2.5" SSD/ HDD
Vægt	:	0.96Kg
Dimensioner	:	56 x 108 x 153 mm

