

19" TFT monitor med 350-nits LCD, støv og spuletæt IP66, Dual AC/DC inputs, Effektiv til industri FEATURES

19" TFT metal monitor LED backlight, IP66
1280 x 1024
350 nits, 1000:1, 5:4
Responstid: 5ms
visnings vinkel: 170°/160°
3 x BNC
2 x DVI-I (29-Pin DVI-D female)
1 x VGA (15-Pin D-sub femlæ)
1 x RS232/422/485 (software selectable terminal block)
100 to 240 VAC, 24 VDC (18 to 30 V)
-15 to 55°C (5 to 131°F)
vægt: 9,700 g
483 x 444 x 82 mm
Panel mounting
RoHS, CRoHS, WEEE
Optional: RS-232: TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
Optional: RS-422: Tx+, Tx-, Rx+, Rx-, GND
Optional: RS-485-2w: Data+, Data-, GND
Optional: RS-485-4w: Tx+, Tx-, Rx+, Rx-, GND



SPECIFICATIONS

Antal farver	:	16.7M (8-bit/color)
Betragtningsvinkel	:	170°/160°
Forsyning	:	100 to 240 VAC, 24 VDC (18 to 30 V)
I/O	:	3 x BNC, 2 x DVI-I, 1 x VGA
Kontrast	:	1000:1, 350 nits, 5:4
Pixels	:	1280 x 1024
Porte	:	1 x RS232/422/485 (software valgt terminal blok)
Vægt	:	9,700 g
Dimensioner	:	483 x 444 x 82 mm
Certifications	:	EMC EN 55032/24

