

Robust DIN-skinne fanless Embedded PC med Intel® Celeron® Processor N3350, 2 COM, LAN, 2 USB og DIO

FEATURES

- Ekstrem omkostningseffektiv fanless Embedded PC
- Intel® Celeron®-processor N3350 1.1GHz
- 2 x COM
- 2 x USB
- 1 x GbE LAN
- 8-bit programmerbar DIO til IoT gateway applikationer
- Bredt temperaturområde fra -40 ° C til + 70 ° C
- 12 til 24 VDC strømindgang
- OVP, UVP, OCP, RPP strømbeskyttelse design



SPECIFICATIONS

CPU	:	Intel® Celeron® processor N3350 (1.1 GHz, Dual Core)
Storage	:	mSATA shared with PCI Express Mini Card slot (option eMMC flash onboard)
Chipset	:	SoC Integrated
Digital I/O	:	1 x DI/DO (8-bit programmable, DB9 female connector)
USB	:	2 x USB 2.0
Driftstemperatur	:	-40°C to +70°C (-40°F to +158°F)
Approval	:	CE FCC Class
Chok/Vibration	:	2 Gms (5 to 500Hz, amplitude 0.35 mm; operation/storage/transport)
Ethernet	:	1 x 10/100/1000 Mbps
Forsyning	:	Terminal, 12 to 24 VDC, 1.15 to 0.62A (13.80 to 14.88W) Protection: OVP (±20%), reverse protection
Hukommelse	:	1 x SO-DIMM DDR3L-1866, up to 8 GB
Luftfugtighed	:	10% to 95% relative humidity, non-condensing



SPECIFICATIONS

OS SUPPORT	:	Windows® 10 IoT, Linux support package, AXView 2.0
PCI	:	1 x full-size PCI Express Mini Card slot with SIM slot (for wireless module) 1 x full-size PCI Express Mini Card slot (for wireless module or mSATA
Porte	:	2 x RS-232/422/485
Udgange	:	1 x VGA
Vægt	:	0.3 kg (0.67 lb)/0.46 kg (1 lb)
Dimensioner	:	(W x D(W x D x H) 31 x 100 x 125 mm (1.22" x 3.93" x 4.92") x H) 31 x 100 x 125 mm (1.22" x 3.93" x 4.92")

