

Isoleret USB til RS485 konverter, -25 °C ~ +75 °C FEATURES

- USB til RS485 konverter, isoleret
- 1 x RS485 7-Pin terminal blok
- 1 x USB-B
- Hastighed: 300 ~ 115200 bps
- Til USB 1.1/2.0 (High Speed)
- 2500 VDC isolation på RS485
- Til DIN skinne montering
- Kræver ikke ekstern strømforsyning
- Input +5 VDC fra USB porten
- OS support WIN 98/ME/2000/XP (32/64-bit)/Vista (32/64-bit)/7 (32/64-bit)/8 (32/64-bit)/10/Linux
- Driftstemp. -25 °C ~ +75 °C
- USB kabel (1,8m) medfølger



SPECIFICATIONS

USB	:	Fully Compliant with the USB 1.1/2.0 (High Speed)
Driftstemperatur	:	-25 °C ~ +75 °C
Andet	:	Power and data flow indicator for troubleshooting
Forsyning	:	No External Power Supply required
Hastighed	:	300 ~ 115200 bps
Isolation	:	2500 VDC Isolation Protection on the RS-485 side
Montering	:	Tiny packaging fits on your DIN-Rail
OS SUPPORT	:	Driver Supports Windows 98/ME/2000/XP (32/64-bit)/Vista (32/64-bit)/ 7 (32/64-bit)/8 (32/64-bit)/10/Linux
Stik	:	RS-485: Removable 7-Pin Terminal Block USB: Type B
Dimensioner	:	(W x H x D) 52 mm x 87 mm x 27 mm

