

## Fanless embedded PC med Intel® Braswell SoC Processor, 1.6GHz, med HDMI

### FEATURES

- Intel® Celeron® N3060, 1.6GHz
- 2 x 204-pin DDR3L SO-DIMM Socket.
- 1600MHz SDRAM op til 8 GB (2GB pre-installed)
- Chipset: SoC Integrated, Intel® HD Graphics 400
- Harddisk: mSATA, MicroSD socket
- 1 x Serial ATA port med 600MB/s HDD transfer rate
- 2 x Realtek 8111HS GbE controllers (LAN chipset)
- 1 x Micro-B RS232 half-duplex
- 4 x USB 3.0 ports, 1 x Micro-B USB 2.0, 2 x RJ-45 ports for GbE
- 2 x HDMI, Max. resolution : 3840 x 2160
- 1 x 3.5mm stereo headphone jack
- Supports 2/4/5.1/7.1 channel configurations via HDMI
- Driftstemperatur:-10 ~ 55 °C, Fugt: 0%-85% RH @ 55 °C
- 0.86 KG, 141 x 34.8 x 107.6
- OS Support: Windows® 7 / Windows® 10 / Linux (Kernel: 3.1X)



## SPECIFICATIONS

|                  |   |                                                                                                                                                                         |
|------------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CPU              | : | Soldered onboard Intel® Celeron® N3060, 1.6GHz                                                                                                                          |
| Chipset          | : | SoC Integrated                                                                                                                                                          |
| Driftstemperatur | : | -10 ~ 55 °C                                                                                                                                                             |
| Chok/Vibration   | : | 3 Grms/5~500Hz/random operation, Operating 50G (11ms), Non-operating 80G with eMMC                                                                                      |
| Grafik           | : | Intel® HD Graphics 400                                                                                                                                                  |
| Harddisk         | : | 1 x mSATA, 1 x MicroSD socket,                                                                                                                                          |
| Hukommelse       | : | 2 x 204-pin DDR3L SO-DIMM socket, supporting 1600MHz SDRAM up to 8GB (2GB DDR3L SO-DIMM pre-installed)                                                                  |
| I/O              | : | 1 x Micro-B RS232 half-duplex, 4 x USB 3.0 ports, 1 x Micro-B USB 2.0, 2 x RJ-45 ports for GbE, 2 x HDMI, 1 x 3.5mm stereo headphone jack, 1 x Half-size Mini-PCle slot |
| Luftfugtighed    | : | 0%-85% RH @ 55 °C (non-condensing)                                                                                                                                      |
| Materiale        | : | Aluminum alloy                                                                                                                                                          |
| Montering        | : | Support VESA-mount                                                                                                                                                      |
| OS SUPPORT       | : | Windows® 7 / Windows® 10 / Linux (Kernel: 3.1X)                                                                                                                         |



## SPECIFICATIONS

|                |   |                      |
|----------------|---|----------------------|
| Strømforsyning | : | DC 19V input         |
| Watchdog       | : | 1~255 levels reset   |
| Vægt           | : | 0.86Kg               |
| Dimensioner    | : | 141 x 34.8 x 107.6mm |
| Certifications | : | CE, FCC Class B      |

