

Embedded PC Intel® Core™ i3-5010U ULT SoC, HDMI
/ DisplayPort, 2 GbE LAN'er, 4 USB 3.0, 2 COM og
PCIe Mini-kort

FEATURES

- Intel® Haswell & Core™ i3-5010U Broadwell ULT SoC
- 204-pin DDR3L-1600 SO-DIMM, op til 8 GB
- Design med fladt design med kompakt størrelse
- 1 RS-232/422/485 og 1 RS-232 port
- En 2,5 "9,5 mm SATA-harddiskdrev og mSATA-grænseflade
- 1 PCI Express Mini-kort-slot
- 4 USB 3.0-porte
- DisplayPort og HDMI med dobbeltvisning understøttet



SPECIFICATIONS

CPU	:	CPU Intel® i3-5010U 2.1 GHz Broadwell ULT SoC
Storage	:	1 x 2.5" 9.5mm SATA HDD drive bay
Chipset	:	SoC Integrated
Driftstemperatur	:	-20°C ~ +50°C (-4°F ~ +122°F) (with W.T. SSD) Humidity 10% ~ 90% , non-condensing
Farve	:	Standard Color Silver-Black
Andet	:	1 x VDC 12V power input connector 1 x ATX power switch 1 x Reset button
BIOS	:	AMI
Approval	:	CE, UL, FCC & VCCI
Chok/Vibration	:	Vibration Endurance 3 Grms with SSD™ (5-500Hz, X, Y, Z directions)
Ethernet	:	2 x 10/100/1000 Mbps Ethernet (Intel® i218LM supports wake on LAN,PXE Boot ROM; i210AT)
Forsyning	:	12Vdc Jack connection
Hukommelse	:	System Memory 1 x 204-pin DDR3L-1600 SO-DIMM, up to 8GB



SPECIFICATIONS

LED	:	1 x orange LED for HDD active
Materiale	:	Construction Aluminum extrusion and heavy-duty steel
Msata	:	1 x mSATA
OS SUPPORT	:	WE8S, WES7, Linux, WIN 10
Porte	:	1 x RS-232/422/485 1 x RS-232
Udgange	:	1 x DisplayPort 1 x HDMI
Watchdog	:	255 levels, 1 ~ 255 sec.
WiFi/WLAN	:	2 x SMA type connector opening for antenna, Without PCI express ethernet controller
Vægt	:	(net/gross) 0.8 kg (1.76 lb)/1.5 kg (3.31 lb)
Dimensioner	:	141.5 mm (5.57") (W) x 106 mm (4.17") (D) x 55 mm (2.17") (H)

