

Trådløs WiFi access point, 5GHz, data transmission
op til 300Mbps , 9-48VDC

FEATURES

- Industriel accespoint med Atheros XSPAN chipset
- IEEE 802.11 a/b/g/n
- 2 x 10/100Base-TX WAN/LAN Ports
- 2 x eksterne antenner
- WLAN single radio
- Tx Power 21 dB for 2.4GHz
- Tx Power 18 bB for 5GHz
- WPA, WPA2, TKIP, AES
- Power Input: 9~48VDC in 6-Pin Terminal Block
- Reverse Polarity Protection
- IP30 Tæthed
- DIN skinne eller væg montering
- Driftstemperatur: 0°C to 60°C
- Dimensioner: 30 x 140 x 95mm
- Vægt: ca 1 KG (0.60 lbs)



SPECIFICATIONS

Chipset	:	Atheros XSPAN
Driftstemperatur	:	-10° to 60° C
Approval	:	EMI, EMS, RF, RF Radiation Exposure, EN60950-1 CNS14336-1, RoHS Compliant
I/O	:	2 x RJ45, 2 x Antenner, 1 x 9-48V DC
IP-Tæthed	:	IP30
Luftfugtighed	:	5 to 95%, (non-condensing)
Materiale	:	Metal
Montering	:	DIN-Rail eller væg montering
Netværk	:	IEEE 802.11 a/b/g/n IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet
Protokol	:	IP, TCP, UDP, ARP, BOOTP, ICMP, HTTP, HTTPS, DNS Proxy, NTP, RADIUS, Dynamic DNS, SNMP
Sikkerhed	:	WPA, WPA2, WPA3, WEP, TKIP, AES
Strømforsyning	:	9~48VDC



**DANBIT**

ANR-AMS-7131

SPECIFICATIONS

Dimensioner	:	30 x 140 x 95mm
Certifications	:	FCC, CE, NCC, RCM



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.