

Fjernmonitor over Ethernet med 24 input porte. 4
Digital input med S0. 6 x Analog input. RS485
Modbus RTU til Modbus TCP. SNMP

FEATURES

- Multi input Data logger for op til 70000 logninger
- 10/100 Mbit Ethernet
- Adgangskodebeskyttet, webbaseret konfiguration og kontrol
- 4 digitale indgange, kompatibel med S0-pulsgrænseflade
- 6 analoge indgange med 0 / 10V og 0 / 20mA
- MODBUS RTU-interface til op til 24 sensorer (registre)
- Op til 24 kanaler til overvågning
- Op til 24 uafhængige alarmer
- SNMP v.2 support - SNMP Trap - alarmvarsler
- HTTP- og SNMP-portændring - HTTP API-kommandoer
- Periodisk HTTP-post af XML / JSON-statusfiler til klientserver-systemer
- MODBUS TCP / IP-understøttelse
- Dynamisk DNS med DynDNS, No-IP og DNS-O-Matic support
- NTP-protokolunderstøttelse
- Forsyningsspænding: 10 til 28V DC



SPECIFICATIONS

Driftstemperatur	:	-20° - +55°C
Hukommelse	:	Internal FLASH memory Settings segment endurance: 100 000 cycles (Every setting change is a memory cycle). Data logger segment endurance: 100 000 cycles of 70000 records. Update segment endurance: 100 000 cycles (updates).
Indgang	:	Isolation: Isolated (1000VDC) Mode: OPEN/CLOSED ("Dry contact") or COUNTER (S0-pulse interface outputs) Maximum input voltage: +5.5VDC Sampling rate: 1mS Digital filtering time interval: 5 to 60000mS
Indgang	:	Isolation: Isolated (1000VDC) Type: Single ended Resolution: 10 bits Mode: Voltage or current loop Input Range: 0/10V or 0/20mA Accuracy: ±1% Sampling Rate: 600mS per channel (averaged value of 100 samples) Input Impedance: 1 mega-ohm (min.)
Luftfugtighed	:	10 to 80% (non-condensing)
Strømforbrug	:	220 mA @ 12 VDC (without RS-485 powering)
Strømforsyning	:	10 til 32V DC
Vægt	:	200g
Dimensioner	:	145 x 90 x 40

