

ANR-LNP-0702G-F-24T

7 ports industriel PoE+ gigabit unmanaged switch, 4 x RJ45, 2 x SFP

FEATURES

- 4 x 10/100/1000Tx IEEE 802.3at PoE+ Compliant with 30W per Port
- 1 x 10/100/1000Tx
- 2 x 100/1000 SFP
- Auto MDI/MDI-X Function
- 14Gbps Back-Plane (Switching Fabric)
- 8K MAC adresse
- 9.6Kbytes Jumbo Frame
- Surge Protection: 2,000 VDC
- ESD Beskyttelse: 6,000 VDC
- Strømforsyning: 12~36VDC
- Indbygget 1 x Relay Output for Power Failure Detection
- IP30 Rugged Metal Case Design
- Din skinne og væg montering
- Driftstemperatur -40° to 75° C
- Dimensioner: 46 x 99 x 142mm
- Vægt: 1.4 Lb



SPECIFICATIONS

Driftstemperatur	:	40° to 75°C
Approval	:	EMI, EMS, RF, RF Radiation Exposure, EN60950-1 CNS14336-1, RoHS Compliant
I/O	:	5 x RJ45 Ports w/ 4*10/100/1000Tx (PSE 30W/Port), and 1*10/100/1000Tx, 2 x 100/1000 SFP Slot
IP-Tæthed	:	Metal, IP30 protection
Luftfugtighed	:	5 to 95%, (non-condensing)
Montering	:	Din skinne og væg montering
Netværk	:	10Base Tx: 2-pair UTP/STP Cat. 3,4,5 100Base Tx: 2-pair UTP/STP Cat. 5 1000Base Tx: 2-pair UTP/STP Cat. 5/5E
Standarder	:	IEEE 802.3 10BaseTx Ethernet IEEE 802.3u 100BaseTx Fast Ethernet IEEE 802.3ab 1000BaseTx Ethernet IEEE 802.3z Gigabit Fiber IEEE 802.3at PoE+
Strømforbrug	:	145 Watts
Strømforsyning	:	12~36VDC, Redundant Input
Switch	:	14,880pps for Ethernet Port 148,800pps for Fast Ethernet Port 1,488,000pps for Gigabit Ethernet Port, 10Gbps Back-Plane (Switching Fabric)
Vægt	:	Unit 1.4 lb. Shipping Weight 1.8lbs





DANBIT

ANR-LNP-0702G-F-24T

SPECIFICATIONS

Certifications : FCC, CE, UL 61010-1, UL 61010-2-201, UL Class 1 Division 2, ISA 12.12.01



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.