

GSM alarm med 2xDIN, 2xAIN og 2xDO. Alarmer til mobiltelefon via SMS eller CALL, APP, 4G LTE

FEATURES

- 2 x Digitale indgange NC/NO Type
- 2 x Analog indgange. 12 bit opløsning, 0-5V, 4-20mA eller 0 - 20mA
- 2 x Relæudgange 5A/30VDC, 5A/250VAC
- 1 x USB-port
- GSM 3G 4G mobilnettet
- 9-36VDC (12V / 300mA)
- Backup Batteri 3.7V 1200mAh
- Driftstemperatur -10- + 70 ° C
- Tilpasset SMS Alarmmeddelelser
- APP til iOS og Android

BEMÆRK LEVERES UDEN SIM KORT!



SPECIFICATIONS

Driftstemperatur	:	-10 to +70 °C
Frekvens	:	GSM 850/900/1800/1900Mhz or 3G UMTS/HSDPA
Indgang	:	2 x Digital input, NC/NO/Edge/Level type, Can be used as Pulse Counters;
Indgang	:	2 Analog Inputs. 12 bit resolution, 0-5V or 0-20mA or 4-20mA;
Input	:	DC 12V/1.5A Range 9-36VDC
Relæ	:	2 X Rated: 5A/30VDC,5A/250VAC
Strømforbrug	:	Standby:12V/70mA; Working Max.: 12V/300mA
Vægt	:	1000 g
Dimensioner	:	168 x 113 x 32.3mm

