

Embedded fanless system med Celeron® CPU N3160  
(1.6 Ghz/4core), optil 8GB, mSATA & SATA SSD  
el.HDD

## FEATURES

Omkostningseffektiv med blæserløs og kabelløs design  
Intel® Celeron® processor N3160 (1.6 GHz/4-core)  
2 x RS-232/422/485 porte  
4 x USB porte  
2 x isolated 10/100/1000 Mbps Ethernet porte  
1 x PoE PD kompatibel med IEEE 802.3at standard LAN 1  
1 x DIO port  
2 x PCI Express Mini Card slots (3G/GPRS & Wi-Fi)  
1 x mSATA & SATA SSD (or HDD)  
12 to 24 VDC  
Vægt: 1.50 KG  
Dimensioner: 48 x 110 x 155 mm  
DIN skinne og væg montering  
OS support: Windows® 7 Embedded, Windows® 8 Embedded, Windows® 8, Windows® 10, Linux support package



## SPECIFICATIONS

|                  |   |                                                                                                             |
|------------------|---|-------------------------------------------------------------------------------------------------------------|
| CPU              | : | intel® Celeron® processor N3160 (1.6 GHz/4-core)                                                            |
| USB              | : | 2 x USB 3.0 2 x USB 2.0                                                                                     |
| Driftstemperatur | : | -20°C to +60°C                                                                                              |
| Farve            | : | Sølv                                                                                                        |
| BIOS             | : | AMI UEFI BIOS                                                                                               |
| Beskyttelse      | : | DC version OVP, reverse protection                                                                          |
| Chok/Vibration   | : | 2 Gms (5 to 500Hz, amplitude 0.35 mm; operation/storage/ transport                                          |
| Harddisk         | : | 1 x mSATA 1 x SATA SSD (or HDD)                                                                             |
| Hukommelse       | : | 1 x DDR3L-1600 SO-DIMM, op til 8GB                                                                          |
| Luftfugtighed    | : | 10% to 95%                                                                                                  |
| Montering        | : | Din skinne og væg montering                                                                                 |
| Netværk          | : | 2 x 10/100/1000 Mbps Ethernet (Intel® i211AT) 1 x PoE PD compliant with IEEE 802.3at standard through LAN 1 |



## SPECIFICATIONS

|                |   |                                                                                                                                                           |
|----------------|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Porte          | : | 2 x RS-232/422/485 (COM 1/2) with DB9, 2 x USB 3.0, 2 x USB 2.0, 2 x 10/100/1000 Mbps Ethernet, DC terminal block: 12 to 24V DC-In, VGA (DB15 connector), |
| Software       | : | AXView 2.0 Intelligent Remote Management Solution for IoT                                                                                                 |
| Strømforsyning | : | DC terminal block: 12 to 24V DC-In PoE: IEEE 802.3at                                                                                                      |
| Trådløs        | : | 1 x Full-size PCI Express Mini Card slot 1 x Full-size PCI Express Mini Card slot with mSATA 1 x SIM card socket 3 x Antenna                              |
| Vægt           | : | 1.50 KG                                                                                                                                                   |
| Dimensioner    | : | 48 x 110 x 155 mm                                                                                                                                         |
| Certifications | : | CE, FCC                                                                                                                                                   |

