

10-Ports industriel unmanaged switch, 2 FTP porte,
EOT: -40° to 75°C

FEATURES

- Supporter 8-Port 10/100Tx
- 2 Gigabit Combo Ports
- 6 x RJ45 Porte 10/100Tx
- 2 x 10/100/100 RJ45
- 2 x 100/1000 SFP Slots
- Supporter Auto MDI/MDI-X
- Non-Blocking Switching Fabric
- 8K MAC Address
- Surge Protection: 2,000 VDC
- ESD Protection: 6,000 VDC
- UL Class I, Division 2 Certified
- Redundant Power Input Design: 12~48VDC
- 1 x indbygget relæ Output til Power Failure advarsel
- IP30 Rugged Metal Case Design
- DIN-skinne og væg montering
- Driftstemperatur EOT: -40° to 75°C



SPECIFICATIONS

Driftstemperatur	:	EOT: -40° to 75°C
Approval	:	EMI, EMS, FCC Class A,
Buffer	:	4Mbps (buffer)
Forbindelse	:	1 removable 6-contact terminal block
Luftfugtighed	:	5 to 95%, (non condensing)
Materiale	:	Metal, IP30 beskyttelse
Netværk	:	10Base Tx: 2-pair UTP/STP Cat. 3,4,5 100Base Tx: 2-pair UTP/STP Cat. 5 1000Base Tx: 2-pair UTP/STP Cat. 5/5E
Porte	:	6*RJ45 Ports w/10/100Tx , 2 *RJ45 Ports w/10/100/1000TX Ethernet and 2*100/1000 SFP Slot
Protokol	:	CSMA/CD
Standarder	:	IEEE 802.3 10BaseTx Ethernet IEEE 802.3u 100BaseTx Fast Ethernet IEEE 802.3ab 1000BaseTx IEEE 802.3z Gigabit Fiber
Strømforbrug	:	10W
Strømforsyning	:	12~48VDC, Redundant Input



**DANBIT**

ANR-LNX-1002C-SFP-T

SPECIFICATIONS

Certifications : FCC, CE, UL 61010-1, UL 61010-2-201, UL Class 1 Division 2, ISA 12.12.01



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.