

ANR-LNX-0500-M12-67+

5-Ports industriel IP67 Switch, M12 connector, 12-48V DC, EOT: -40°C to 75°C

FEATURES

- 5 x 10/100Tx RJ45 hurtig Ethernet
- M12 (D-coded hun) Connector IP67 beskyttet
- IP67 Plastic Case Design
- RJ45 Port Support Auto MDI / MDI-X
- Auto Negotiation hastighed, Half / Full Duplex
- Store-and-Forward Switching Architecture
- Strømforsyning: 12~48VDC
- Power Polarity Reverse Protection
- Overload Current Protection
- DIN-Skinne eller væg montering
- Dimensioner: 37.13 x 215.73 x 32.8 mm (W x H x D)
- Driftstemperatur: EOT: -40°C to 75°C



SPECIFICATIONS

Driftstemperatur	:	EOT: -40°C to 75°C
Approval	:	EMI, EMS, FCC Part 15 Subpart B Class A, CE EN 55022 Class A
Chok/Vibration	:	IEC60068-2-27, IEC60068-2-6
Forbindelse	:	Power: 1*M12, 5-pin A-coded, Male
Luftfugtighed	:	5% to 95%, (non-condensing)
Materiale	:	Plastic, IP67 protection
Montering	:	DIN-skinne og væg montering
Porte	:	5*10/100T(X) M12, 4-pin D-coded, Female, auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection
Protokol	:	CSMA/CD
Standarder	:	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet
Strømforbrug	:	500mWatts
Strømforsyning	:	12 - 48VDC





DANBIT

ANR-LNX-0500-M12-67+

SPECIFICATIONS

Certifications : FCC, CE, UL 61010-1 (Pending), UL 61010-2-201 (Pending)



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.