

ANR-LNP-1002G-SFP-24

10-Ports Gigabit Switch med PoE+ unmanaged, 8 x RJ45 og 3 x SFP, 12-36VDC, 48-55VDC

FEATURES

- 8 x 10/100/1000Tx RJ45
- PoE+ (30W/port) IEEE 802.3at PoE
- 2 x 100/1000 SFP porte
- Auto MDI/MDI-X Funktion
- Store-and-Forward Switching Architecture
- 20Gbps Back-Plane (Switching Fabric)
- 8K MAC Address Table
- 9.6Kbytes Jumbo Frame
- Surge Protection: 2,000 VDC
- ESD Protection: 6,000 VDC
- UL Class I, Division 2 Certified
- Forsyningsspænding: 48~55VDC
- Indbygget relæ Output for Power Failure
- IP30 Rugged Metal Case Design
- DIN-Skinne og Væg montering
- Driftstemperatur STD:-10° til 70°C



SPECIFICATIONS

Ethernet	:	8 x RJ45 Ports w/10/100/1000Tx (PSE 30W/Port)
Fiber	:	2 x 100/1000 SFP Slot
Luftfugtighed	:	5% to 95%, (non-condensing)
Materiale	:	Metal IP30 protection
Montering	:	DIN-skinne og væg montering
Netværk	:	10Base Tx: UTP/STP Cat. 3,5 100Base Tx: UTP/STP Cat. 5 1000Base Tx: UTP/STP Cat.5/5e/6
Protokol	:	CSMA/CD
Standarder	:	IEEE 802.3 10BaseTx Ethernet IEEE 802.3u 100BaseTx Fast Ethernet IEEE 802.3ab 1000BaseTx IEEE 802.3z Gigabit Fiber IEEE 802.3at PoE+
Strømforbrug	:	145 Watts @ 12V 200 Watts @ 24V (Full Load w/ PoE)
Strømforsyning	:	12-36VDC
Dimensioner	:	46 x 99 x 142 mm
Certifications	:	FCC, CE, UL 508, UL Class 1 Division 2, ISA 12.12.01

