

## 12-Port industrial PoE+ Gigabit unmanaged switch FEATURES

- 8 x 10/100/1000Tx RJ45 (30W/port)
- 2 x 10/100/1000Tx RJ45
- 2 x 100/1000 SFP porte
- Auto MDI/MDI-X Funktion
- Store-and-Forward Switching Architecture
- 24Gbps Back-Plane (Switching Fabric)
- 8K MAC Address Table
- 9.6Kbytes Jumbo Frame
- Surge Protection: 2,000 VDC
- ESD Protection: 6,000 VDC
- UL Class I, Division 2 Certified
- Strømforsyning: 48~55VDC
- Indbygget relæ Output til Power Failure
- IP30 Rugged Metal Case Design
- DIN-Skinne og Væg montering
- Driftstemperatur STD: -10° to 70° C



## SPECIFICATIONS

|                  |   |                                                                                                                                      |
|------------------|---|--------------------------------------------------------------------------------------------------------------------------------------|
| Driftstemperatur | : | STD: -10° to 70°C                                                                                                                    |
| Buffer           | : | 7,926pps (default)                                                                                                                   |
| Chok/Vibration   | : | IEC60068-2-32, IEC60068-2-27                                                                                                         |
| Ethernet         | : | 10*10/100/1000Tx RJ45 (w/8*PSE: 30W/Port)                                                                                            |
| Fiber            | : | 2 x 10/100/1000 SFP Slot                                                                                                             |
| Forbindelse      | : | 1 removable 6-contact terminal block                                                                                                 |
| Luftfugtighed    | : | 5% to 95%, (non-condensing)                                                                                                          |
| Materiale        | : | Metal, IP30 protection                                                                                                               |
| Montering        | : | DIN-skinne og væg montering                                                                                                          |
| Protokol         | : | CSMA/CD                                                                                                                              |
| Standarder       | : | IEEE 802.3 10BaseTx Ethernet IEEE 802.3u 100BaseTx Fast Ethernet IEEE 802.3ab 1000BaseTx IEEE 802.3z Gigabit Fiber IEEE 802.3at PoE+ |
| Strømforbrug     | : | 10 Watts Full load w/PoE 215W@48V / 255W@51~55V                                                                                      |



**DANBIT**

ANR-LNP-1202G-SFP

## SPECIFICATIONS

Dimensioner : 46 x 99 x 142 mm (W\*D\*H)

Certifications : FCC, CE, UL 61010-1, UL 61010-2-201, UL Class 1 Division 2, ISA 12.12.01



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.