

ANR-LNP-1604G-SFP-T

16-Ports Gigabit Switch med PoE+, unmanaged 12 x RJ45 porte og 4 x FTP porte, -40° til +75°C, 48-55VDC FEATURES

- 12 x 10/100/1000Tx RJ45
- PoE+ (30W / port) IEEE 802.3at
- 4 x 100/1000 SFP porte
- Store-and-Forward Switching Architecture
- 8K MAC Address Table
- 12.2Kbytes Jumbo Frame
- Surge Protection: 2,000 VDC
- ESD Protection: 6,000 VDC
- Forsyningsspænding: 48~55VDC
- Indbygget relæ Output til Power Failure
- IP30 Rugged Metal Case Design
- DIN-Skinne og Væg montering
- Driftstemperatur: -40° to 75°C



SPECIFICATIONS

Driftstemperatur	:	-40° to 75°C
Buffer	:	4 Mbit
Chok/Vibration	:	IEC60068-2-32, IEC60068-2-27
Ethernet	:	12*RJ45 Ports w/10/100/1000Tx (w/PSE: 30W/port), auto negotiation speed, Full/Half duplex, and auto MDI/MDIX connection
Fiber	:	4*100/1000 SFP Slots
Forbindelse	:	1 removable 6-contact terminal block
Luftfugtighed	:	5% to 95%, (non-condensing)
Materiale	:	Metal, IP30 protection
Protokol	:	CSMA/CD
Relæ	:	24 VDC, 1A resistive
Standarder	:	IEEE 802.3 10BaseTx Ethernet IEEE 802.3u 100BaseTx Fast Ethernet IEEE 802.3ab 1000BaseTx IEEE 802.3z Gigabit Fiber IEEE 802.3af/at Power over Ethernet
Strømforbrug	:	16W; (376W w/full PSE load)



**DANBIT**

ANR-LNP-1604G-SFP-T

SPECIFICATIONS

Dimensioner	:	59 x 99 x 142 mm (W*D*H)
Certifications	:	FCC, CE



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.