

ANR-FCU-2802SC

Mediekonverter RJ45 til fiber. RJ45 10/100/1000Mbit.
Fiber 1000Mbit, SC, Multi Mode, op til 550 meter,
5VDC

FEATURES

- 1000Mbit Multi Mode Mediekonverter til RJ45
- 1 x RJ45 10/100/1000BaseT
- 1 x 1000BaseSX/LX med SC stik Multi Mode
- Back-Pressure in Half-Duplex
- Auto MDI/MDI-X function
- Store-and-Forward mechanism
- Op til 220m / 550m
- Dimensioner: 97 x 70 x 26 mm
- Driftstemperatur: 0 - +50°C
- Strømforsyning: 5VDC/2A medfølger



SPECIFICATIONS

Driftstemperatur	:	0° C to 50° C
Afstand	:	FCU-2802SC: 220m ~ 550m FCU-2802SC-S10: 10km
Fiber	:	FCU-2802SC: SC / Multi-Mode FCU-2802SC-S10: SC / Single-Mode
Interface	:	1 x 1000BaseT RJ-45 Port (Auto-MDI/MDI-X) Twisted Pair 1 x 10/100/1000BaseT Port 1 x 1000BaseSX/LX Port
LED	:	Power, TP Link/ACT, Fiber Link/ACT
Luftfugtighed	:	5% to 90% (non-condensing)
Standarder	:	IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX IEEE 802.3ab 1000BaseT IEEE 802.3z 1000BaseSX/LX
Strømforbrug	:	5 Watts
Strømforsyning	:	5V DC, 2A
Dimensioner	:	97 x 70 x 26mm
Certifications	:	FCC Class A, CE Class A

