

ANR-LNX-2602G-SFP

26-Ports industriel gigabit unmanaged switch, IP40, 1U, 19" Rackmount

FEATURES

- 24 x 10/100/1000Tx RJ45
- 2 x Gigabit Combo Porte
- 2 x 10/100/1000Tx RJ45
- 2 x 100/1000 SFP Slots
- Auto MDI/MDI-X Function
- Store-and-Forward Switching Architecture
- 8K MAC Address Table
- 9.6Kbytes Jumbo Frame
- Surge Protection: 2,000 VDC
- ESD Protection: 6,000 VDC
- Redundant Power Input Design: 90~264VAC
- 1 x indbygget Relæ Output til Power Failure
- IP40 Rugged Metal Case Design
- 1U 19" Rackmount design Support
- Driftstemperatur: -10° to 70° C



SPECIFICATIONS

Driftstemperatur	:	STD: -10° to 70° C
Approval	:	EMI, EMS, FCC Part 15 Subpart B Class A, CE EN 55022 Class A
Buffer	:	4Mbps (buffer)
Chok/Vibration	:	IEC60068-2-27, IEC60068-2-6
I/O	:	26 x RJ45 10/100/1000Tx, 2 x 100/1000 SFP Slots
Luftfugtighed	:	5 to 95%, (non-condensing)
Materiale	:	Metal, IP40 beskyttelse
Montering	:	1U 19" Rackmount
Netværk	:	10Base Tx: UTP/STP Cat. 3,5 100Base Tx: UTP/STP Cat. 5 1000Base Tx: UTP/STP Cat.5/5e/6
Protokol	:	CSMA/CD
Standarder	:	IEEE 802.3 10BaseT Ethernet IEEE 802.3u 100BaseTX Fast Ethernet IEEE 802.3ab 1000BaseT IEEE 802.3z 1000Base-X Gigabit Fiber
Strømforbrug	:	24Watt



**DANBIT****ANR-LNX-2602G-SFP**

SPECIFICATIONS

Dimensioner : 440 x 44 x 200 mm (W x H x D)



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.