

ANR-LNP-1002G-SFP

10-Ports industriel PoE+ unmanaged switch med 2 SFP porte og 8 RJ45 porte.

FEATURES

- 8 x 10/100/1000Tx RJ45 IEEE 802.3at PoE+
- 2 x 100/1000 SFP porte
- Auto MDI/MDI-X Funktion
- Store-and-Forward Switching Architecture
- 20Gbps Back-Plane (Switching Fabric)
- 8K MAC Address Table
- 9.6Kbytes Jumbo Frame
- Surge Protection: 2,000 VDC
- ESD Protection: 6,000 VDC
- UL Class I, Division 2 Certified
- Strømforsyning: 48~55VDC
- Indbygget relæ Output for Power Failure
- IP30 Rugged Metal Case Design
- DIN-Skinne og Væg montering
- Driftstemperatur STD: -10° to 70° C



SPECIFICATIONS

Driftstemperatur	:	STD: -10° to 70°C
Ethernet	:	8 x RJ45 Ports w/10/100/1000Tx (PSE 30W/Port)
Fiber	:	2 x 100/1000 SFP Slot
Luftfugtighed	:	5 to 95%, (non-condensing)
Materiale	:	Metal, IP30 protection
Montering	:	DIN-skinne og væg montering
Netværk	:	10Base Tx: 2-pair UTP/STP Cat. 3,4,5 100Base Tx: 2-pair UTP/STP Cat. 5 1000Base Tx: 2-pair UTP/STP Cat. 5/5E
Protokol	:	CSMA/CD
Standarder	:	IEEE 802.3 10BaseTx Ethernet IEEE 802.3u 100BaseTx Fast Ethernet IEEE 802.3ab 1000BaseTx IEEE 802.3z Gigabit Fiber IEEE 802.3at PoE+
Strømforbrug	:	210 Watts @ 48V 250 Watts @ 51-55V (Full Load w/ PoE)
Strømforsyning	:	48~55VDC, Redundant Input
Dimensioner	:	46 x 99 x 142 mm (W*D*H)



**DANBIT**

ANR-LNP-1002G-SFP

SPECIFICATIONS



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.