

Siemens 19" panel monitor, IP65 front Touch, 1366 x 768 pixels, 24VDC, DisplayPort, VGA

FEATURES

Siemens 6AV7862-2BE00-0AA0
DEMO MODEL - mindre slagskader i alu rammen (hjørnerne)
19" HMI monitor med LED backlight 24V DC
Panel montering
Widescreen display
Opløsning: 1366 x 768
2 x USB 2.0
1 x VGA
1 x Displayport (DP)
1 x USB touch interface
IP65 (front)
LED backlight
Touch: analog resistive
Montering: VESA 100 x 100
Forsyningsspænding: 24V DC
Driftstemperatur: 0 - 45 grader
Dimensioner: 473 x 297 mm
Monteringsplade dimensioner: 455 x 279 mm



SPECIFICATIONS

Driftstemperatur	:	0 - 45 grader
Chok/Vibration	:	5 M/s - 250 M/s
Forsyning	:	24V DC
I/O	:	2 x USB 2.0, 1 x VGA, 1 Displayport, 1 x USB touch
IP-Tæthed	:	IP65 ved fronten
Luftfugtighed	:	85 procent
Materiale	:	Aluminun
Strømforbrug	:	19 - 60W
Touch	:	Analog resistive
VESA standard	:	100 x 100
Vægt	:	Uden pakning 5.1 kg
Dimensioner	:	473 x 297 x 455 x 279mm





DANBIT

MON19-P-TU-DP

SPECIFICATIONS



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.