

Kompakt 400VA UPS med 3 x SCHUKO udgange FEATURES

- Single Phase
- Linje-Interaktiv
- GreenPower UPS bypass Technology
- 230 ± 10%
- Schuko
- 400VA
- overbelastnings
- 3 x Schuko ud
- kørselstid på 60W 28Min
- Runtime på 90W 16 min
- Forseglet Bly-syre batteri
- MAC, WINDOWS, LINUX
- Mål: 280 x 174 x 84 mm



SPECIFICATIONS

USB	:	1 port HID compliant
Driftstemperatur	:	0 ~ 40 degrees
Alarm	:	Power On, Line Mode, Battery Mode, Bypass Mode, Low Battery, Overload, UPS Fault
Approval	:	CE
Beskyttelse	:	Surge suppression 125 Joules, EMI/RFI ,
Effekt	:	250Watt , 400VA
Ethernet	:	yes, up to 1GB
Forsyning	:	230 ± 10%
Frekvens	:	50 ± 1% 60 ± 1%
LED	:	Power On, Line Mode, Battery Mode, Bypass Mode, Low Battery, Overload, UPS Fault
Materiale	:	Plastic
Overvågning	:	Software for Windows, MAC, Linux



**DANBIT**

UPS400

SPECIFICATIONS

Udgange	:	3 x SCHUKO
Dimensioner	:	84 x 174 x 280 mm



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.