

MODBUS/TCP Master/Slave til seriel RTU
Slave/Master, Gateway, 1 x RJ45 1 x RS485/422
isoleret, -25 - +75°C, PoE eller 12 - 48VDC

FEATURES

- Kompakt Modbus/TCP til RTU/ASCII Gateway med PoE
- Skal ikke programmeres
- 1 x RJ45 10/100Mbps
- 1 x RS485/422 (skrueterminal)
- Baud rate op til 115.200 bps
- Self-tuner til RS485/422
- Automatisk sende-/modtage-retning på RS485
- IEEE 802.3af - PoE (PD)
- Forsyningsspænding u/PoE: 12 - 48VDC 2Watt
- DC stik er Power Jack 5,5/2,1mm
- Mål: 90 x 52 x 27 mm
- DIN-beslag
- Driftstemperatur: -25 - +75°C



SPECIFICATIONS

Driftstemperatur	:	-25 - +75°C
Forsyning	:	PoE (PD)
Kabinet	:	Plast med DIN-beslag og terminal-blokke
Mål og vægt	:	95 x 52 x 26 mm
Porte	:	1 x RJ45 10/100Mbps
Porte	:	1 x RS485 / RS422
Spænding	:	Uden PoE, 12 - 48VDC, 2Watt

