

MODBUS/TCP Master/Slave til serial RTU
Slave/Master, Gateway, 1 x RJ45 1 x RS232/485/422
isoleret, -25 - +75°C, PoE, 12 - 48VDC

FEATURES

- Kompakt Modbus/TCP til RTU/ASCII Gateway med PoE
- Skal ikke programmeres
- 1 x RJ45 10/100Mbps
- 1 x RS232 / RS485 / RS422 (terminalblok)
- Vælg kun 1 COM port som interface
- 3-pin RS232 (RX, TX, GND)
- Baud rate op til 115.200 bps
- Self-tuner til RS232
- IEEE 802.3af - PoE (PD)
- Forsyningsspænding u/PoE: 12 - 48VDC 2Watt
- Mål: 90 x 52 x 27 mm
- DIN-beslag
- Driftstemperatur: -25 - +75°C



SPECIFICATIONS

Driftstemperatur	:	-25 - +75°C
Forsyning	:	PoE (PD)
Kabinet	:	Plast med DIN-beslag og terminal-blokke
Mål og vægt	:	95 x 52 x 26 mm
Porte	:	1 x RJ45 10/100Mbps
Porte	:	1 x RS232 / RS485 / RS422 (kun en kan vælges)
Spænding	:	Uden PoE, 12 - 48VDC, 2Watt

