

PIR bevægelsesføler, temperatur- og lys-niveau programmeres, relæ-udgang, M485, MODBUS RTU, DCON, 10 - 30VDC. Indendørs

FEATURES

- Bevægelses-føler, lys-registrering, temperatur-føler til energi-styring
- Kan tilsluttes energi-styring, lokale-lysstyring via RS485 porten
- Med kraftig indbygget relæ til simpel lys-aktivering 250VAC (1.500 Watt T8)
- 360° bevægelsesregistrering - op til 8 m i diameter og 4 meter højde
- Tidsforsinkelse / Lysfølsomhed er justerbar
- Temperaturføler - måling af stuetemperatur eller brandalarm
- Relæudgang at tænde for lyset via PIR/lys-styrke og temperatur-følerne
- RS485 2-tråds kommunikations-bus
- DCON og Modbus RTU-protokoller
- Loft overflademonteret design
- Forsyningsspænding: 10 - 30VDC ca. 2W
- Mål: Ø121 x 52 mm
- IP20



SPECIFICATIONS

Serial	:	1x RS-485 DCON, Modbus RTU
Driftstemperatur	:	0 to +35°C
Andet	:	Hardware: 8-step Switch-selectable (seconds): 6, 16, 33, 66, 131, 262, 524, 1049 Software: 16-step (seconds): 2, 4, 6, 8, 16, 33, 49, 66, 131, 262, 393, 524, 1049, 2097, 3146, 4194
IP-Tæthed	:	IP20
Luftfugtighed	:	10 to 90% RH, Non-condensing
Lysstyrke	:	Hardware: 2 mode (Dawn and dust) / Software: 5-step
Montering	:	Ceiling mounting
Relæ	:	1x Power Relay, Form C; NO: 10 A @ 250 VAC NC: 6 A @ 250 VAC
Strømforsyning	:	10 to 30 VDC (1.3 W)
Temperatur	:	Measurement Range: -25 ~ +100°C Accuracy: ±2°C
Range	:	Distance: 4 meters Max. 360°; Diameter 8 meters Max.
Dimensioner	:	121 mm x 52 mm

