

17" TFT-LCD Modulær Panel PC med 8. Gen. Intel® Core™ U Series Processor, 9~48VDC

FEATURES

- 17" 1280 x 1024 (SXGA) TFT-LCD
- True Flat IP65 Kompatibel
- Resistiv Touch
- Intel® Core™ i3-8145ue Dual Core Processor (4M Cache, op til 3,90 GHz) (Standard)
- Intel® Core™ i5-8365 quad Core Processor (6M cache, op til 4,10 GHz) (option)
- 2x DDR4 SO-DIMM, Understøtter op til 2400MHz, 64GB maks
- Integreret USB 3.2 Gen 2 understøtter op til 10 Gb/s
- M.2 E Key til trådløst modul eller Intel CRF-modul
- Understøtter tændingsfølerfunktion (IGN) (option)
- Understøtter 2x PoE+ -funktion (option)
- Designet med robust aluminium Die-casting Front Bezel
- Panel / VESA / Rack Mounting
- 9~48VDC via 3-pin Terminal Block



SPECIFICATIONS

Storage	:	2x 2.5" HDD/SSD Drive Bay (SATA 3.0), Supports RAID 0/1
USB	:	3x USB 3.2 Gen2 (Type A), 4x USB 3.0, Type-A, 2x USB 2.0 (Type A)
Driftstemperatur	:	-20°C to 70°C
Andet	:	Fanless Design
DIO	:	16x Isolated DIO (8x DI/8x DO), 20-Pin Terminal Block
Forsyning	:	9~48VDC via 3-pin Terminal Block
Grafik	:	Integrated Intel® UHD Graphics 620
Hukommelse	:	2x DDR4 2400 MHz 260-Pin SO-DIMM Socket Supports up to 64 GB (un-buffered and non-ECC)
Kontrast	:	800 : 1
Lyd	:	Realtek® ALC888-GR
Lysstyrke	:	350 cd/m2
Netværk	:	2 x RJ45 (GbE1: Intel I219LM, GbE2: Intel I210IT)



SPECIFICATIONS

Porte	:	4x RS-232/422/485 with Auto Flow Control (Supports 5V/12V), DB9
Skærm	:	17" (5:4) 1280 x 1024
Touch	:	Resistive 5-wire
Udvidelser	:	2x Full-size Mini-PCIe Socket, 1x M.2 2230 E Key, 1x Front Accessible, 4x Antenna Hole SIM
Vægt	:	7.9 kg
Dimensioner	:	450 x 350 x 76 mm

