

Embedded PC, Pentium® N4200 op til 2,50 GHz, 4x
RS-232/422/485, 9~48VDC

FEATURES

- Pentium® Processor N4200
- 1x DDR3L SO-DIMM MAX. Op til 8 GB
- Triple Independent Display (1x CDS, 1x VGA, 1x DisplayPort)
- 1x 2.5" SATA Drive Bay, 1x MSATA Socket
- Rich I/O (2x LAN, 4x USB, 4X COM, 8X Isoleret DIO)
- 2x Fuld størrelse Mini-PCIe Expansion Socket
- Understøtter 2xPOE + -funktion (med option modul)
- Understøtter tændingsfølerfunktion (IGN) (med option modul)
- Understøtter CDS-teknologi til konvertibelt panel PC
- Indbygget to 2W interne højttalere
- 9~48VDC via 3-pin Terminal Block
- Tilkøb strømforsyning - se Tilbehør



SPECIFICATIONS

CPU	:	Intel® Pentium® N4200
Video	:	1x CDS, 1x VGA, 1x DisplayPort
USB	:	4x USB 3.0 (Type-A)
Driftstemperatur	:	-40°C to 70°C
Antenne	:	4x Antenna Holes
Forsyning	:	9~48VDC via 3-pin Terminal Block
Grafik	:	Integrated Intel® HD Graphics 505
Hukommelse	:	1x DDR3L 1333/1600/1866 MHz 204-Pin SO-DIMM Socket (8GB max)
Lyd	:	Realtek ALC888-GR
Montering	:	Wall / VESA / CDS / DIN Rail
mPCIe	:	2x Full-size Mini-PCIe Sockets
Msata	:	1x mSATA Socket (SATA 3.0, Shared by Mini-PCIe Socket)



SPECIFICATIONS

OS SUPPORT	:	Windows 10
Porte	:	4x RS-232/422/485 with Auto Flow Control Support 5V/12V, DB9
SIM kort	:	1x SIM Socket
SSD	:	1x 2.5" HDD/SSD Drive Bay (SATA 3.0)
Vægt	:	1.49 kg
Dimensioner	:	204.5 x 149 x 41.5 mm

