

2MP ATEX Zone 1 og 2 CLASS IIC kompakt IP kamera i 316L stålhus. IP68, NMEA 4X, Zoom 2.8-12mm. PoE eller 12VDC

FEATURES

ATEX certificeret IP kamera i stålhus
2 Megapixel
Motor-Zoom fra 2.8 - 12mm @F1.6
NMEA-4X, IP68/IP69
H.264+/ H.264/ M-JPEG Compression
Smart Focus System med remote fokus justering
DMR digital støjreduktion
PoE Power over Ethernet, 2,88W
PoE 9W med heater on ved -40°C
Dag og nat manuel switch tidskontrol
Driftstemperatur -40°C - +65°C
Varmelegeme kobles ind ved -40°C
Micro SD Card Backup op til 64GB
2-way Audio
Support iPhone/Android/Mac
SDK for Software Integration
Free Bundle 36 Ch Recording Software
Mål: L145 x Ø95 mm
Vægt: 3.8kg
Labellængde: 4 meter



SPECIFICATIONS

IP-Tæthed	:	IP68 / IP69
Kamera	:	1/28" Sony True WDR Starvis CMOS Sensor
Linse	:	2.8 - 12mm, 4.2 Zoom
Materiale	:	AIST 316L Stainless Steel
Mål og vægt	:	145 x ø95 mm, 3.8kg
Opløsning	:	1920x1080 @ 30Hz 2MP
Certifications	:	Zone 1 og 2 IIC T6 Group (Gas), Zones 21 og 22 IIIC T85 deg C

