

12.1" Industrial Panel PC, i3/i5 CPU, USB, RS232,
Touch, 450/500/1000 nits versioner, 9~36Vdc
forsyning mange optioner!

FEATURES

12.1" TFT

CPU Gen.6 i3 standard (i5 option)
med eller uden Touch resistive, projected
capacitive 7H anti scratch overflade
1 x 260-pin SO-DIMM DDR4 2100Mhz max. 16GB
2 x USB 3.0
1x 2½" SSD SATA Bay
1 x Mini PCIe slot full size
1xDB9 RS232/422/485, COM1, 1x RS-232 DB9 COM
2
2 x RJ45 Gbe LAN RJ45
IP66 front
Vesa mount 100x100
319x245x51.7mm
1 x 3 pin DC 9~36Vdc
Windows IOT support
Kontakt os vedr. version og bestykning



SPECIFICATIONS

USB	:	2 x USB 3.0 type A
Driftstemperatur	:	0~50°C / -20~60°C (option)
Back-up	:	UPS battery 21W/10.8W/1.95Ah OPTION!
Approval	:	CE / FCC, Class A / UL
Ethernet	:	2 X RJ45 GbE
Forsyning	:	DC 9~36Vdc MAX 47W
Kontrast	:	1500:1(800x600), 1000:1(1024x768) (1000 nits 700:1)
Lyd	:	line out
Materiale	:	Aluminium
Montering	:	Panel Mount, Vesa mount 100x100
Opløsning	:	MAX 800x600 /1024x768
OS SUPPORT	:	Windows IOT



SPECIFICATIONS

Skærm	:	12.1" 800x600/1024x768 Depends on selected display
SSD	:	2½" BAY SATA
Touch	:	Needs to be ordered! Resistive, Projected capacitive or glass
Nits	:	450/500/1000 nits option needs to be specified when ordering
Vægt	:	2.6Kg
Dimensioner	:	319x245x51.7mm

