

Blæserløst system, 9./8. generation i7/i5/i3
Celeron®-processor, Intel® Q370, USB, RS232, VGA,
HDMI, DIN-MOUNT

FEATURES

Industriel blæserløs Celeron, i3/i5,i7 CPU-
understøttelse (LGA 1151)
Gen. 8/9
Chipset Q370
1x RS232/422/485. VALGFRI! ISOLERET
RS232/422/485, Skal bestilles separat!
4 USB 3.1 Gen. 2
2 x USB 2.0
1 x USB (intern, 180D type A til licensnøgle, op til
30 mm)
2 x ETH Intel i211-AT & i219-LM (Option! flere kan
bestilles)
VGA, HDMI udgang
19~30Vdc
OPTION: vægbeslag eller DIN-beslag
83,4x192x230 mm (BxHxD)
Arbejdstemperatur -10°C til +60°C, BEMÆRK
KRÆVER RAM OG SSD også specificeret for -10°C til
+60°C Bestil separat!
OS understøtter Windows 10 og Linux



SPECIFICATIONS

CPU	:	9th/8th gen Intel® Core™ processor, up to 65W
Chipset	:	Q370
USB	:	4 x USB 3.1 Gen 2 2 x USB 2.0 1 x USB 2.0 (internal, 180D type A for license key, up to 30mm
Driftstemperatur	:	-10°C to +60°C (+14°F to +140°F) with Intel®, 9th/8th gen Intel® Core™ and W.T. HDD/SSD
BIOS	:	AMI
Approval	:	CE/FCC
Ethernet	:	2 x 10/100/1000 Mbps (Intel® i211-AT & i219-LM) OPTION! More LAN ports available from extension I/O modules
Hukommelse	:	2 x DDR4-2666/2400 MT/s un-buffered SO-DIMM, up to 64GB
Materiale	:	Aluminum extrusion heavy-duty cold-rolled steel
Montering	:	Wall mount as option, DIN mount as option
mPCIe	:	Intel® Q370: 1 x Full-size PCI Express Mini Card slot (USB & PCIe interface) or 1 x M.2 Key B 3050 socket
Mål og vægt	:	Weight (net/gross) 3.82 kg (8.43 lb)/4.78 kg (10.55 lb)



SPECIFICATIONS

Porte	:	1 x RS-232/422/485 (default RS-232) OPTION! More COM ports available from extension I/O modules
Spænding	:	Type: ATX/AT Input: 24 VDC (uMin=19V/uMax=30V)
TPM	:	Supports TPM 2.0
Udgange	:	1 x VGA 1 x HDMI
AMT	:	12
Dimensioner	:	Dimensions (W x H x D) 83.5 x 192 x 230 mm (3.28" x 7.54" x 9.04")

