

Blæserløs indlejret pc med 11. generations Intel® i7 CPU (andre versioner: i3 og i5)

FEATURES

- 11. generations Intel® i7 CPU (valgfrit: i3, i5)
- 2 x 260-bens DDR4 SO-DIMM (maks. 64 GB)
- 1 x M.2 M-nøgle
- 1 x 2,5" harddisk/SSD
- 16 x I/O
- 4 x KOM
- 3 x LAN (2xPoE)
- 4 x USB 3.1
- Fjernbetjent strømforsyning
- 1 x DVI-D
- 1 x HDMI
- 1 x DP
- TPM 2.0
- Sikker opstart
- Montering: Vægmontering (valgfrit: DIN-skinne eller VESA)
- Strømindgang: 9~36 VDC
- Dimensioner: 210x180x70mm (BxDxH)
- Driftstemperatur -20 ~ 60 °C Med luftstrøm



SPECIFICATIONS

CPU	:	Intel® Core™ i3-1115G4E
CPU	:	Intel® Core™ i5-1145G7E
CPU	:	Intel® Core™ i7-1185G7E
Memory Type	:	DDR4
Max. Memory Capacity	:	64
Memory Channels	:	Dual Channel
Storage	:	1 x 2.5" HDD/SSD
Storage	:	1 x M.2 2242/2280
Graphics	:	Intel® Iris® Xe Graphics
LAN Chipset	:	2 x Intel® i211AT
LAN Chipset	:	1 x Intel® 225LM
Digital I/O	:	8 x DI & 8 x DO w/ 1.5KV isolation



SPECIFICATIONS

Expansion	:	1 x M.2 E-Key 2230
Expansion	:	1 x mPCIe
Power Input	:	DC 9~36V
Max. Power Consumption	:	120W
Video	:	1 x HDMI 2.0
Video	:	1 x DisplayPort 1.4
Video	:	1 x DVI-D
USB	:	4 x USB-A 3.2
Serial	:	2 x DB-9 (RS232)
Serial	:	2 x DB-9 (RS232/422/485)
LAN	:	2x 1Gb LAN



SPECIFICATIONS

Audio	:	1 x Mic-in & 1 x Line out
Driftstemperatur	:	-20 ~ 60°C
Storage Temp.	:	-40 ~ 70°C (-40 ~ 158°F)
Operating Humidity	:	10-95% @ 60°C (non-condensing)
Vibration	:	5~500Hz 3 Grms
Shock	:	40G peak acceleration (11 m sec. duration), operation
Shock	:	80G peak acceleration (11 m sec. duration), nonoperation
Shock	:	According to IEC 60068-2-27
Vægt	:	3.7kg
Dimensions	:	210 x 180 x 70 mm
Certifications	:	CE/ FCC Class A

