

**DANBIT**

EPC-I14X2E8U4SVDD

Intel® 14/13/12. Gen. rugged embedded PC, 6x
2.5GbE LAN, USB-C, PCIe Cassette, MezzIO™ interface,
-25 ~ 70 °C, 8-48 VDC

FEATURES



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.

Understøtter Intel® 14./13./12. generations Alder Lake Core™ CPU (LGA1700, 35/65W TDP)
Intel® Q670E-chipsæt, integreret Intel® UHD Graphics 770
Maks. 64 GB DDR5 4800 MHz SDRAM (2 x SO-DIMM)
Op til 6 x 2,5 GbE/GbE LAN med skruelås (skal bestilles separat. 1 x 2,5 GbE + 1 x GbE på 2-ports modeller / 5 x 2,5 GbE + 1 x GbE på 6-ports modeller)
Kan bestilles IEEE 802.3at PoE+ PSE på 2.5GbE port 3-6, samlet PoE-budget 100 W
1 x USB 3.2 Gen2x2 (20 Gbps) Type-C med skruelås
4 x USB 3.2 Gen2x1 (10 Gbps) type-A + 2 x USB 3.2 Gen1x1 (5 Gbps) type-A
2 x USB 2.0-porte
1 x VGA, 1 x DVI-D, 1 x DisplayPort (op til 4K opløsning)
COM: 2 x RS-232/422/485 (COM1/COM2, softwarekonfigurerbar) + 2 x RS-232 (COM3/COM4)
2 x interne SATA-porte til 2,5" HDD/SSD (RAID 0/1 på E/P/DE-modeller) eller 1 x hot-swap 2,5" SSD/HDD + 1 x intern SATA (LP-modeller)
1 x M.2 2280 (PCIe Gen4 x4) til NVMe SSD (op til ~7000 MB/s)
Patenteret kassette til udvidelse med PCIe/PCI-kort:
Version 1: 1 x PCIe x16 Gen3
Version 2: 2 x PCIe x16 Gen3
Version 3: 1 x PCI-slot
1 x mini PCIe (fuld størrelse)
1 x M.2 2242/3052 B med nano-SIM til 4G/5G-modem
1 x udvidelig (ekstra COM, digital I/O, mere GigE/PoE, USB osv.)
8-48 V DC-indgang via 3-benet klemrække
Fjernbetjent tænding/watchdog/LED-udgang via separat 3-bens klemrække
Ventilatorløs, industrielt design - testet i henhold til MIL-STD-810G for vibrationer og stød
Driftstemperatur (afhængig af CPU-konfiguration):
-25 ~ 70 °C med 35 W CPU
-25 ~ 50 °C med 65 W CPU (fuld TDP)
Vægmontering som standard, DIN-skinmontering som ekstraudstyr
Certificering: CE/FCC Klasse A
Mange versioner, kontakt vores salgsafdeling



**DANBIT**

EPC-I14X2E8U4SVDD



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.

SPECIFICATIONS

CPU	:	14th-12th gen. Supporting Intel® 14th-Gen Core™ CPU (LGA1700 socket, 65W/35W TDP) - Intel® Core™ i9-14900/ i9-14900T - Intel® Core™ i7-14700/ i7-14700T - Intel® Core™ i5-14500/ i5-14400/ i5-14500T - Intel® Core™ i3-14100/ i3-14100T
Chipset	:	Intel® Q670E platform controller hub
USB	:	1x USB 3.2 Gen2x2 (20 Gbps) port in type-C connector with screw-lock 4x USB 3.2 Gen2x1 (10 Gbps) ports in type-A connectors 2x USB 3.2 Gen 1x1 (5 Gbps) ports in type-A connectors 2x USB 2.0 ports
Ethernet	:	There is more versions!1x 2.5G Ethernet by I225 and 1x Gigabit Ethernet by I219 with screw-lock OPTION:2.5G Ethernet by I225 and 1x Gigabit Ethernet by I219 with screw-lock
Forsyning	:	1x 3-pin pluggable terminal block for 8 to 48V DC input 1x 3-pin pluggable terminal block for remote control and PWR LED output
Grafik	:	Integrated Intel® UHD Graphics 770 (32EU)
Hukommelse	:	Up to 64 GB DDR5 4800 SDRAM (two SODIMM slots)
Lyd	:	1x 3.5 mm jack for mic-in and speaker-out
M.2	:	1x M.2 2280 M key NVMe socket (PCIe Gen4x4) for NVMe SSD, 1x M.2 2242/3052 B key socket with SIM slot for M.2 5G/ 4G module
mPCIe	:	1x full-size mini PCI Express socket
PCI	:	Needs to be ordered 1x PCI slot in Cassette
PCI	:	Needs to be ordered 2 solutions: 1x PCIe x16 slot@Gen3, 16-lanes PCIe signals in Cassette (Nuvo-9002E/ 9006E) 2x PCIe x16 slots@Gen3, 8-lanes PCIe signals in



SPECIFICATIONS

Porte	:	2x software-programmable RS-232/ 422/ 485 ports (COM1/ COM2) 2x RS-232 ports (COM3/ COM4)
SSD	:	2x internal SATA port for 2.5" HDD/ SSD installation, supporting RAID 0/ 1
TPM	:	Supports dTPM 2.0
Udgange	:	1x VGA, supporting 1920 x 1200 resolution 1x DVI-D, supporting 1920 x 1200 resolution 1x DisplayPort, supporting 4096 x 2304 resolution
Udvidelser	:	1x expansion port for special IO modules
AMT	:	Supports Intel vPro/ AMT 16.0
Dimensioner	:	2 sizes contact sales 240 mm (W) x 225 mm (D) x 90 mm (H) (Single slot solution E/ P series) 240 mm (W) x 225 mm (D) x 110.5 mm (H) DUAL slot solution

