

IPP19-J1900

PanelPC, IP65 front med Capacitive touch og J1900  
quad core CPU

## FEATURES

- 19" TFT-LCD 250 nits
- Opløsning: 1280x1024
- Frontpanel IP65
- Intel® Celeron® J1900, Quad-core, op til 2,42 GHz
- 4 GB RAM onboard
- 2 x RJ45
- 1 x HDMI
- 4 x USB 2.0
- 6 x RS-232 (2x DB9, 4x terminal)
- 9-36V DC via terminal
- 20 ~ 60° C driftstemperatur
- Panelmontering/ 75 mm VESA montering
- Mål 437,27 x 316,27 x 60,3 mm



**SPECIFICATIONS**

|                      |   |                                       |
|----------------------|---|---------------------------------------|
| CPU                  | : | J1900,Quad-core, Up to 2.42GHz        |
| Memory Type          | : | DDR3                                  |
| Max. Memory Capacity | : | 8                                     |
| Power Input          | : | DC 12~36V                             |
| USB                  | : | 4 x USB 2.0                           |
| Serial               | : | 2x DB9 RS232, 4x screw terminal RS232 |
| Driftstemperatur     | : | -20° C ~ +60° C                       |
| Ethernet             | : | 2 x GbE LAN RJ45                      |
| Hukommelse           | : | 8GB MAX                               |
| Lysstyrke            | : | 250 nits                              |
| mPCIe                | : | 1 x Mini PCIe full size               |
| Opløsning            | : | 1280 x 1024                           |



## SPECIFICATIONS

|                     |   |                   |
|---------------------|---|-------------------|
| SATA                | : | 1 x SATA til 2.5" |
| Skærm               | : | 19" TFT-LCD       |
| Antal Video Udgange | : | 1                 |
| Antal LAN Porte     | : | 2                 |
| Antal USB           | : | 4                 |
| Antal Serial        | : | 6                 |

