

Programmerbar Industrial IoT Controller med 1 digitale indgang og 1 digitale udgang, 2 COM porte FEATURES

- CPU QuadCore Cortex A72 (ARM v8) 64 bit SoC 1,5 GHz
- RAM 4GB LPDDR4 standard (1/2/8 valgfri)
- 32GB EMMC Flash-hukommelse
- 1 x Micro HDMI
- 2x USB 3.0, 2x COM (1xRS-232/422/485, 1xRS-232/485)
- RTC: Realtidsur
- 1x digital indgang tør (åben/luk)/våd (0-3V/10-30V) kontakt
- 1x digital udgang (120VAC @0,5A, 240VAC @0,25A, 30VDC @1A)
- DC 9~32V indgang DC Jack eller terminalindgang



SPECIFICATIONS

CPU	:	Broadcom BCM2711 QuadCore Cortex A72 (ARM v8) 64 bits SoC @ 1.5G
Digital I/O	:	Digital Input * 1 Pin (Active High / Active Low Selectable); Digital Output * 1 Pin (Active High / Active Low Selectable)
Video	:	Micro HDMI * 1 (4Kp60fps with audio)
USB	:	USB 3.0 * 2
Serial	:	Port 1: RS-232/422/485 * 1; Port 2: RS-232/485 * 1
Driftstemperatur	:	-20°C□75°C
Netværk	:	10/100/1000 Mbps Giga Lan * 1 (RJ45); 10/100Mbps * 1 (RJ45)
OS SUPPORT	:	Linux OS
SSD	:	32GB EMMC Flash
Strømforsyning	:	DC 9~32V, 1000mA@12V (DC Jack or Terminal Input)
RAM	:	4GB LPDDR4 Standard
Dimensioner	:	170 * 110 * 30 mm

