

ESW16G-DIN

Industriel Gigabit Ethernet-switch - 16 porte

FEATURES

- 16 RJ45 Ethernet-porte
- 10/100/1000 Mbps med automatisk justering af MDI/MDI-X
- DIN-skinne og vægmontering
- Metalkapsling klassificeret til IP30
- Dobbelt strømindgang for redundans
- 8K MAC adresse tabel
- Driftstemperatur -40 til 75 C grader
- 12 til 48VDC indgang



SPECIFICATIONS

Driftstemperatur	:	-40 ~ 75 degrees C
Alarm	:	One relay output for power failure. Alarm relay current carry ability: 1A @ 24V DC
Hastighed	:	10/100/1000Mbps
IP-Tæthed	:	IP30
Luftfugtighed	:	5 ~ 95% (non-condensing)
Montering	:	DIN-rail kit and wall-mount kit
Strømforbrug	:	DC input: Max. 3.4 watts/11.6BTU (System on) Max. 8.7 watts/29.7BTU (Full loading)
Strømforsyning	:	Dual 12~48V DC, 24V AC
Connector	:	Removable 6-pin terminal block for power input - Pin 1/2 for Power 1 - Pin 3/4 for fault alarm - Pin 5/6 for Power 2
Vægt	:	743g
Dimensioner	:	66 x 107 x 152 mm

