

USB-C™ PD GaN Multiport-bordoplader (65 W) sort 2x USB-C, 2x USB-A-porte

FEATURES

MAKS. i alt 65 watt

GaN teknologi

110-240Vac

2 x USB-C

2 x USB-A AC (QuickCharge)

maksimal strømkapacitet

3 A max. ydeevne 65 W

Produktion:

USB-C™ PD1 (enkelt) max. 65,0W

5,0 V maks. 3,0 A (15,0 W) DC

9,0 V maks. 3,0 A (27,0 W) DC

12,0 V maks. 3,0 A (36,0 W) DC

15,0 V maks. 3,0 A (45,0 W) DC

20,0 V maks. 3,25A (65,0 W) DC

USB-C™ PD2 (enkelt) max. 18,0 W

5,0 V maks. 3,0 A (15,0 W) DC

9,0 V maks. 2,0 A (18,0 W) DC

12,0 V maks. 1,5 A (18,0 W) DC

USB-A QC1 max. 18,0 W

5,0 V maks. 3,0 A (15,0 W) DC

9,0 V maks. 2,0 A (18,0 W) DC

12,0 V maks. 1,5 A (18,0 W) DC

USB-A QC2 max. 18,0 W

5,0 V maks. 3,0 A (15,0 W) DC

9,0 V maks. 2,0 A (18,0 W) DC

12,0 V maks. 1,5 A (18,0 W) DC

Dimension 87,2 (L) x 91 (B) x 19,5 (H) mm

Vægt 154 g

