

3000Mbit 2.4/5GHz udendørs Wifi Access Point,
Gateway, Repeater, Wi-Fi Mesh. IP67 alu kabinet,
PoE+ -40 - +70°C

FEATURES

- Udendørs robust Dual Band Access Point mm.
- AP, Gateway, Repeater, Wi-Fi Mesh
- 2.4GHz og 5GHz, 600/2400Mbit (3000Mbit)
- Op til 256 klienter Wi-Fi 6
- 1 x RJ45 Gigabit port PoE+
- IEEE 802.11ac 2T2R - Wave 2
- Op til 20dBm (EIRP)
- 4 x N-hun stik
- IP67 støbt aluminum kabinet til mastmontering
- Driftstemperatur: -40 - +70°C
- Real-time Wifi kanal analyser
- Mål: 295 x 231 x 80 mm
- Vægt: 2.5kg
- Forsyning: PoE, 48V/0.5A (PoE+)



SPECIFICATIONS

Driftstemperatur	:	-40~ 70 degrees C
Andet	:	Mesh Auto Channel Selection 5-level Transmit Power Control: Max (100%), Efficient (75%), Enhanced (50%), Standard (25%) or Min (15%) Client Limit Control, Coverage Threshold Wi-Fi channel analysis chart Seamless Roaming Beamforming BSS Coloring
Antenne	:	Built-in four N-type connectors
Interface	:	PoE WAN/LAN: 1 x 10/100/1000BASE-T, auto-MDI/MDIX, 802.3at PoE In
IP-Tæthed	:	IP67
Kanaler	:	20MHz, 40MHz, 80MHz, 160MHz
Modes	:	Access Point Gateway Repeater WISP Mesh
PoE	:	48V 0.5A, IEEE 802.3at PoE+, < 15W
Sikkerhed	:	Enable/Disable SSID Broadcast Wireless Max. 32 MAC address filtering User Isolation
VLAN	:	IEEE 802.1Q VLAN (VID: 1~4094) SSID-to-VLAN mapping to up to 4 SSIDs
Dimensioner	:	231 x 80 x 295 mm

