

Wi-Fi 6 Dual Band Wireless Access Point 3000 Mbps med PoE og 2 LAN-porte

FEATURES

Dual Band 802.11ax 3000 Mbps Loftmonteret
trådløst adgangspunkt
Maks. trådløs hastighed på 2400 Mbps (5 GHz) og
600 Mbps (2,4 GHz)
Understøtter op til 256 samtidige klientbrugere
2 x 10/100/1000BASE-T RJ45 port
4 x intern 4dBi-antenne (2,4G x2, 5G x2)
Tilstande: AP, Gateway, Repeater
WPA3 / WPA2 / WPA-understøttelse
Loftsmontage
Mål: 185,82 x 185,82 x 36,6 mm
Understøtter 48V DC PoE og 12V DC input
Driftstemperaturområde: -20 til 55°C
Vægt: 380 g



SPECIFICATIONS

LAN	:	2 x 10/100/1000BASE-T RJ45 port
Antal	:	256 clients (200 is suggested, depending on usage)
Antenne	:	4 x Internal 4dBi antenna (2.4G x2, 5G x2)
Båndbredde	:	20MHz, 40MHz, 80MHz, 160MHz
Forsyning	:	48V DC IN, 0.5A, IEEE 802.3at PoE+ (WAN/PoE were changed port) 12V DC IN, 1.5A from DC Jack (5.5 x 2.1mm)
Modes	:	Access Point Gateway Repeater WISP Mesh
Montering	:	Ceiling Mount
Sikkerhed	:	WPA3 Personal, WPA2/WPA3 Personal, WPA2 Personal (AES), WPA2 Personal (TKIP), WPA2 Personal (TKIP+AES), WPA/WPA2 Personal (AES), WPA/WPA2 Personal (TKIP), WPA/WPA2 Personal (TKIP+AES), WPA2 Enterprise, WPA/WPA2 Enterprise
Dimensioner	:	185.82 x 185.82 x 36.6 mm
Certifications	:	CE, RoHS

